

# DynoFlex

## Natural Tan

**DESCRIPTION:** Safecoat DynoFlex is a unique, water based, low odor elastomeric sealer that comes in a paste-like compound for sealing seams, joints and cracks in new and old heating and air conditioning ducts, and for repairing metal roofs and asphalt shingles. Also comes in a sprayable form that can be used over **Safecoat DynoSeal** as a topcoat for roofs and decks.

Safecoat DynoFlex is highly resistant to harsh weather and temperature changes. It remains flexible and prevents leaks even after exposure to the elements or contraction due to weather. It is resistant to gasoline, oil, grease, fungi, acids, alkalines and flame spread. Safecoat DynoFlex is also a superb sound deadener.

**PRODUCT NUMBER AND CONTAINER SIZE:** 51173 (quart) and 51373 (five gallon).

**USE ON:** Safecoat DynoFlex is recommended for new and old heating and air conditioning ducts, metal roof cracks, damaged asphalt shingles, mobile home roofs and similar areas. In the sprayable form, it is recommended as a topcoat for **Safecoat DynoSeal**.

### ADVANTAGES / SIGNIFICANT BENEFITS:

- Effective, easy to use.
- Non-offensive to installer and occupant.
- When used in conjunction with **SafeChoice Super Clean** and **SafeChoice X-158**, DynoFlex is a full system for sealing, cleaning and maintaining all heating and air conditioning ducts.
- Safely used by and for the chemically sensitive.
- Very low VOC content, meets or exceeds all federal and state air quality regulations, including California.

**APPLICATION:** Always have adequate ventilation. All areas to be coated should be clean and dry. Remove all oil, dirt, dust, rust and loose residue. When possible clean with a not toxic, biodegradable and odorless cleaner like **SafeChoice Super Clean**. Old asphalt shingles should be power washed prior to treatment. Allow all surfaces to dry completely before applying DynoFlex. Apply DynoFlex at 15 mils wet directly from the container without dilution. Use a brush, squeegee-type applicator or trowel and smooth evenly to produce a uniform and seamless coat. Two coats provides additional protection.

**COVERAGE:** 100 square feet per gallon at 15 mils thickness.

**CLEAN-UP:** Clean tools and equipment while they are still wet with a solution of **SafeChoice Super Clean** and warm water.

**DRYING/CURING TIME:** To touch within 2 hours. Cures hard in 24 hours.

**LIMITATIONS:** Do not apply when ambient or surface temperature is below 55 degrees F. Avoid application in direct hot sun, which may cause premature dryout. If product has thickened in container add a small amount of water and stir to return product to original paste consistency. Safecoat DynoFlex does not contain formaldehyde preservatives. Do not contaminate. When not in use keep container closed.

**HEALTH PRECAUTIONS:** As with all coatings and stains, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation. *If you are chemically sensitive, always test for personal tolerance.*

**LIMITED LIABILITY:** The great variation between environmental factors, possible surfaces and application techniques, and the lack of control we have over such matters, must affect our policies. Safecoat products are guaranteed not to be defective when applied and used in accordance with instructions. However, liability, whether express or implied, is limited solely to replacement of product or refund of purchase price and shall under no circumstances include liability for labor costs or consequential damages. Because of the variety of circumstances affecting each job, it is the user's responsibility to determine the suitability and safety of the product for any particular application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. **We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.**