



Naturals Thinner

**PRODUCT NUMBER AND
CONTAINER SIZE**
40299 Qt/40199 Gal

DESCRIPTION: Safecoat Naturals^a Thinner is specially formulated to be used as a diluent and reducer for all Safecoat Naturals^a plant-based clear oil products, as necessary for the particular application. It is designed to reduce the solids content of the primary coating to promote penetration and leveling. It is also a very suitable clean-up medium for oil-coated tools.

INGREDIENTS: Unlike other products used for similar purposes, Safecoat Naturals^a Thinner is benzene free and contains no aromatic compounds. Its primary component is a unique cosmetic and food processing grade compound, highly refined to reduce offgassing and toxicity. Non-Flammable.

LIMITATIONS: Thinning products such as Safecoat Naturals Penetrating Oil with Safecoat Naturals Thinner may improve flow, absorption and drying, but will reduce solids, potentially affecting performance of the coating. Do not freeze. Always conduct sample patches to assure suitability for use under the applicable conditions. Unused contents should be kept in a closed container in a cool, dry place out of direct sunlight.

HEALTH PRECAUTIONS: Keep container tightly closed and out of the reach of children. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. If splashed on skin or eyes, flush with plenty of water for 15 minutes. If you are chemically sensitive, always test for personal tolerance before using.

AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF SPRAY VAPORS AND SPRAY MIST.

WARNING: Spontaneous combustion danger! This product is used in conjunction with other products containing vegetable oils. By itself, it is not flammable or subject to spontaneous combustion. However, rags, steel wool, sanding dust or waste soaked with oil may spontaneously catch fire if improperly discarded or stored. Immediately after each use, place rags, steel wool, paper, cardboard, sanding dust and other oil soaked waste in a sealed, water filled metal container to prevent heat build-up and fire. When drying, allow oil soaked materials to spread out in open air to prevent fire.

PHYSICAL DATA:

Physical Description:	Liquid, slight mild odor.
% Volatile by Volume:	100%
Solubility in Water:	Slight
% Volatile by Weight	100%
VOC Material:	815 g/l

HAP's (Hazardous Air Pollutants) zero

If you are chemically sensitive, always test for personal tolerance.

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 T: 619.239.0321
Available exclusively through AFM approved retailers worldwide

AFM
safecoat
Building A Healthier World