



SafeChoice Carpet Seal

**PRODUCT NUMBER AND
CONTAINER SIZE**
61120 Gal

DESCRIPTION: SafeChoice® Carpet Seal is a topical sealer designed to prevent the outgassing of harmful chemicals used in carpet backing. These chemicals include such known carcinogens as formaldehyde, toluene, benzene, xylene and styrene. Carpet Seal is odor-free and, when properly applied, effectively blocks outgassing for up to five cleanings or one year.

USE ON: SafeChoice Carpet Seal is generally suitable for all synthetic carpets and rugs. Because of variations in materials and production processes used by different manufacturers, you should always spot test to insure compatibility with your carpet. Wool fibers generally do not react well to water based products, so **SafeChoice Carpet Seal is not recommended for wool.**

APPLICATION: Carpet should be vacuumed and cleaned prior to application of Carpet Seal. Use not toxic, odorless SafeChoice Carpet Shampoo. Follow technical data sheet for use. Immediately after shampooing apply SafeChoice Carpet Seal liberally but evenly (while carpet is still damp) using a hand-held pump sprayer (similar to a garden-type sprayer). Do not oversaturate. SafeChoice Carpet Seal cannot be used on a dry carpet. Work SafeChoice Carpet Seal into the fibers with a rotary brush, polishing machine or clean garage broom, just enough to assure complete and uniform contact. **UPON COMPLETION, CLOTH DRY FIBER TOPS TO PREVENT FORMATION OF WHITE FILM AS PRODUCT DRIES.**

Even coverage and wiping surface is essential. When SafeChoice Carpet Seal is to be applied to a carpet not just immediately cleaned, prior to application be sure to dampen carpet with clear water using a hand-held pump sprayer. The drying and curing process may be accelerated by using conventional heating methods. Do not permit traffic on the carpet until dry to touch. Periodic carpet shampooing may be performed as required. After four or five cleanings or one year, re-application of SafeChoice Carpet Seal may be necessary to ensure outgassing containment. NOTE: Before using SafeChoice Carpet Guard the first time, test in small inconspicuous areas to confirm compatibility and color fastness.

COVERAGE: One gallon of SafeChoice Carpet Seal covers approximately 300 square feet for medium to tight weave carpet.

CLEAN-UP: Rinse with clear water.

DRYING/CURING TIME: In moderate temperatures and humidity four to six hours to the touch - total cure time twenty-four hours. Cool temperatures and/or high humidity may

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

ADVANTAGES / SIGNIFICANT BENEFITS:

- Fights indoor air pollution by stopping the outgassing of toxic materials from carpet backing - the only product in the world so designed.
- Especially important for professional maintenance people who maintain centrally-ventilated buildings where occupants are subject to the effects of all toxic discharges within the building, including those from carpet and building and maintenance products.
- Odorless - pleasant for user and occupant.
- Resists water borne stains.
- Safely used by and for the chemically sensitive.

LIMITATIONS: Not recommended for wool or velour carpet. It is very important to cloth wipe the top of the carpet fiber after application to prevent formation of white film upon drying. Do not permit traffic on the carpet until dry to the touch. Always spot test carpet on inconspicuous locations for color fastness and compatibility. When using carpet products it is advisable to put small squares of aluminum foil under furniture legs until carpet is thoroughly dry.

HEALTH PRECAUTIONS: As with all cleaning products, keep container tightly closed and out of the reach of children. Do not ingest. If swallowed, drink two (2) glasses of water to dilute. In case of eye contact, flush immediately with plenty of water for 15 minutes. If you are chemically sensitive, always test for personal tolerance.

PHYSICAL DATA:

Physical Description:	Clear odorless liquid
pH	12.3
% Volatile by Weight:	95%
Solubility in Water:	Complete
VOC Material less H2O:	zero
HAP's (Hazardous Air Pollutants)	zero

If you are chemically sensitive, always test for personal tolerance.