



DynoFlex

WATER BASED/COVERAGE: One gallon of Safecoat DynoFlex covers approximately 100 square feet at 15 mils thickness.

**PRODUCT NUMBER AND
CONTAINER SIZE**
51173 Gal/51373 5g pail

DESCRIPTION: Safecoat® DynoFlex is a unique, water based, low odor elastomeric sealer formulated in a paste-like compound for sealing seams, joints and cracks in new and old heating and air conditioning ducts, and for repairing metal roofs and asphalt shingles. Safecoat DynoFlex is highly resistant to harsh weather and temperature changes. It remains flexible and prevents leaks even after exposure to the elements or contraction due to weather. Safecoat DynoFlex is resistant to gasoline, oil, grease, fungi, acids, alkalines and flame spread. It is also a superb sound deadener. increase drying time.

USE ON: Safecoat DynoFlex is recommended for new and old heating and air conditioning ducts, metal roof cracks, damaged asphalt shingles, mobile home roofs and similar areas.

APPLICATION: Always have adequate ventilation. All areas to be coated should be clean and dry. Remove all oil, dirt, dust, rust and loose residue. When possible clean with a not toxic, biodegradable and odorless cleaner like SafeChoice Super Clean. Old asphalt shingles should be power washed prior to treatment. Allow all surfaces to dry completely before applying DynoFlex. Apply DynoFlex at 15 mils wet directly from the container without dilution. Use a brush, squeegee-type applicator or trowel and smooth evenly to produce a uniform and seamless coat. Two coats provide additional protection. Note: these instructions are intended to be general only and not exhaustive. The applicator should determine which preparation and techniques are best suited to the specific surface.

ADVANTAGES / SIGNIFICANT BENEFITS:

- Effective, easy to use.
- Non-offensive to installer and occupant. When used in conjunction with SafeChoice Super Clean and SafeChoice X-158, DynoFlex is a full system for sealing, cleaning and maintaining all heating and air conditioning ducts.
- Safely used by and for the chemically sensitive.
- Very low VOC content, meets or exceeds all federal and state air quality regulations, including California.

CLEAN-UP: Clean tools and equipment while they are still wet with a solution of SafeChoice Super Clean and warm water.

DRYING/CURING TIME: To touch within 2 hours. Cures hard in 24 hours.

LIMITATIONS: Unlike conventional sealers, Safecoat sealers are made without formaldehyde preservatives or toxic mildewcides or fungicides. Do not contaminate. Store in airtight containers. Do not use when indoor or surface temperature is below 55°F. Avoid application in direct hot sun, which may cause premature dry-out. If product has thickened in container add a small amount of water and stir to return product to original paste consistency. Keep from freezing.

HEALTH PRECAUTIONS: As with all coatings and stains, keep container tightly closed and out of the reach of children. Do not take internally. Always use adequate ventilation. If you are chemically sensitive, always test for personal tolerance.

PHYSICAL DATA:

% Volatile by Volume:	44.73
Solubility in Water:	Dilutable
% Volatile by Weight	42.17
VOC Material:	29 g/l
VOC Material less H2O:	50 g/l
HAP's (Hazardous Air Pollutants)	zero

**If you are chemically sensitive, always
test for personal tolerance.**

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 T: 619.239.0321
Available exclusively through AFM approved retailers worldwide

AFM
safecoat
Building A Healthier World