

# Installation Guidelines

PRODUCT NUMBER  
CONTAINER SIZE

WATER BASED/COVERAGE: One gallon covers approximately 450 square feet. 72000 Pint/72100 Gal

## USE ON:

Unsealed interior wooden surfaces. Colors include Walnut, Golden Oak, Warm Cherry, Pecan, Nutmeg, Honey Maple, Cognac, Red Mahogany, Warm Oak, White Pickle and Jacobean.

## LIMITATIONS:

Safecoat stains are made without formaldehyde preservatives. Do not contaminate. Store in air-tight containers. Do not use when indoor temperature is below 55 degrees F. Do not freeze. **Thick application, high humidity or conditions other than normal will cause Safecoat to dry and cure more slowly.**

## SURFACE PREPARATION:

Wood surface should be cleaned of dirt, dust, grease, wax, silicone, soap and oil, and completely free of mold, mildew or fungus contamination. **To avoid lapping and extend wet edge time over large areas, water dampen the wood surface just before applying DuroTone.** Because of wide variations in the way different woods accept stain, we particularly recommend that users always test in small, inconspicuous areas for appearance and compatibility before application to the entire surface.

## APPLICATION:

Before using, stir Safecoat DuroTone well, then apply as is stirring occasionally during use. Inter-mix (boxing) all containers of the same color to ensure uniformity before applying.

Apply with the grain using a brush or pad applicator always keeping a wet edge. Note: these instructions are intended to be general only and not exhaustive. The applicator should determine what preparation and techniques are best suited to the specific surface.

## COVERAGE:

One gallon of Safecoat DuroTone covers approximately 450 square feet in one coat depending on surface porosity and the intensity of the stain color desired.

## DRYING/CURING TIME:

Re-coatable after 2 hours in normal conditions. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 55 degrees F.

## CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

## HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

## PHYSICAL DATA:

VOC Material: 28.9 g/l  
VOC Material Less Water: 249.9 g/l

HAP's (Hazardous Air Pollutants) zero

All numbers are maximums. Actual numbers may be less. To recycle or properly dispose of stain in your community call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

**If you are chemically sensitive, always test for personal tolerance.**

Test samples available here:

[www.thegreendesigncenter.com/product/afm-2oz-samples/](http://www.thegreendesigncenter.com/product/afm-2oz-samples/)



**LIMITED LIABILITY:** Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

**American Formulating and Manufacturing** 3251 Third Ave., San Diego, CA 92103 [www.afmsafecoat.com](http://www.afmsafecoat.com).