

Installation Guidelines

WATER BASED/COVERAGE: See specifications below.

USE ON:

This not-toxic, indoor-outdoor flexible emulsion type of caulking compound is designed to replace oil caulk and putty for windows, cracks, tub and shower enclosures and general maintenance. It will not dry out or crack and does not release any solvents or harsh odors. Provides a water-proof, easy-to-install sealant with excellent initial and permanent adhesion and is paintable with water based paint. **Product is best used within six months of purchase.**

LIMITATIONS:

Safecoat products are made without formaldehyde preservatives. Do not contaminate. Do not use when indoor temperature is below 55 degrees F. Do not freeze. Do not paint with oil based paint. **Thick application, high humidity or conditions other than normal will cause Safecoat to dry and cure more slowly.**

SURFACE PREPARATION:

Prime and seal surfaces completely before application of caulk to protect against undue absorption into substrate. All surfaces to receive caulk and overlays must be sound, intact and cleaned of any grease, oils, dust, dirt, wax, unsound prior caulk and other foreign materials.

APPLICATION:

Apply Safecoat Multi-Purpose Caulk directly from tube or container with no dilution. If working from bulk container, apply with a pastry decorating bag, bulk caulking gun or mortar joint filler. Install firmly into opening and joints pressing to insure contact with faces. Tool with knife or spatula to smooth and level the sealant surface using rubbing alcohol. Because Safecoat does not use toxic mildewcides, fungicides, preservatives or solvent softening agents, material can solidify if unused with one year of purchase.

CLEAN-UP:

Clean tools and equipment while they are still wet with rubbing alcohol.

DRYING/CURING TIME:

Under normal conditions, 24 hours for full cure. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 55 degrees F.

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Boiling Point:	NA
Melting Point:	N/A
Volatile by Volume:	0%
% Volatile by Weight:	0%
VOC Material:	Less than 19 g/l @240°

HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**

Test tubes available here:

www.thegreendesigncenter.com



LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. **American Formulating and Manufacturing** 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.