

Usage Guidelines

If you are chemically sensitive, always test for personal tolerance.

USE ON:

Synthetic carpets and rugs, because of variations in materials and production processes used by different manufacturers, you should always spot test to insure compatibility with your carpet. Not recommended for wool.

DO NOT USE ON:

On wool carpeting.

DILUTION PER GALLON OF WATER:

Light cleaning - 3 fluid ounces.

Medium cleaning - 5 fluid ounces.

Heavy cleaning - 8 fluid ounces.

One gallon of diluted solution will clean approximately 300 square feet.

COVERAGE: One gallon covers 300 sf.

APPLICATION:

SafeChoice Carpet Shampoo should be applied using a hand-held pump sprayer. One similar to a garden sprayer is most effective. Prior to application vacuum carpet thoroughly. Using the applicable dilution rate specified above, spray the carpet evenly, saturating the surface. Allow the shampoo ten minutes to fully penetrate. Then extract the shampoo with very clean, very hot water. By extracting with only clean, hot water the carpet is not only cleaned more effectively but the removal of residue from prior cleanings is accomplished. While the foregoing procedure yields the best results, SafeChoice Carpet Shampoo may also if desired be added to any shampooing or carpet cleaning machine.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

HEALTH PRECAUTIONS:

As with all cleaners, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description: Clear, odorless

pH: 9.5

Solubility in Water: Complete

% Volatile by Weight: N/A

VOC Material less H₂O: 0 g/l

HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**

Test samples available by request.



Safechoice products are made without formaldehyde preservatives and are HAPs free. Do not contaminate. Do not use when indoor temperature is below 55 degrees F. Do not freeze.

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. **American Formulating and Manufacturing** 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.

Usage Guidelines

If you are chemically sensitive, always test for personal tolerance.

61130 Gal

USE ON:

Synthetic carpets and rugs, because of variations in materials and production processes used by different manufacturers, you should always spot test to insure compatibility with your carpet. Can also be used on synthetic fabrics commonly used on furniture. Not recommended for wool or velour.

DO NOT USE ON:

On wool carpeting.

PREPARATION:

Carpet should be vacuumed and cleaned using SafeChoice Carpet Shampoo to remove, as much as possible, the petrochemical residue from the fibers. After cleaning, seal carpet with SafeChoice Carpet Seal, then allow the carpet to dry thoroughly before proceeding with application of SafeChoice Lock Out. For old carpeting follow the same procedure of vacuuming and cleaning with SafeChoice Carpet Shampoo. For carpets exceeding four years in age use of SafeChoice Carpet Seal may be optional. Carpet must be completely dry whether or not SafeChoice Carpet Seal is required.

COVERAGE: One gallon covers 300 sf.

APPLICATION:

Using a hand-held pump sprayer (similar to a garden sprayer), spray a fine mist of SafeChoice Lock Out evenly and uniformly over the entire carpet surface. Do not oversaturate. Allow the carpet to dry to touch before permitting floor traffic.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

DRYING/CURING TIME:

Two to four hours in moderate heat and humidity. Cool temperatures and/or high humidity may increase drying time.

HEALTH PRECAUTIONS:

As with all sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description: White dries clear
pH: 9.1
Solubility in Water: Complete
% Volatile by Weight: 95%
VOC Material less H2O: 0 g/l
HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**

Test samples available by request.



Safechoice products are made without formaldehyde preservatives and are HAPs free. Do not contaminate. Do not use when indoor temperature is below 55 degrees F. Do not freeze.

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.