

Installation Guidelines

USE ON:

Porous mineral containing surfaces such as pavers, concrete slabs, block, stone, stucco and plasters under 10 pH.

LIMITATIONS:

Safecoat sealers are made without formaldehyde preservatives. Do not contaminate. Store in airtight containers. Do not use when indoor temperature is below 55 degrees F. Do not freeze. **Thick application, high humidity or conditions other than normal will cause Safecoat to dry and cure more slowly.**

SURFACE PREPARATION:

Clean surfaces of dirt, grease, mildew and oil.

Surface should be completely dry before application.

APPLICATION:

Before using, stir Safecoat Penetrating WaterStop well, then apply as is.

Apply with a brush, pad, roller or hand held pump sprayer.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

DRYING/CURING TIME:

Re-coatable after 2 hours in normal conditions. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 55 degrees F

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description: No odor, clear
% Volatile by Volume: 96.19%
Solubility in Water: Dilutable
% Volatile by Weight: 96.55%
VOC Material: 0 g/l
VOC Material less H2O: 0 g/l
HAP's (Hazardous Air Pollutants) zero

If you are chemically sensitive, always test for personal tolerance.

Test samples available here:

www.thegreendesigncenter.com/product/afm-2oz-samples/

