

Installation Guidelines

PRODUCT NUMBER
CONTAINER SIZE
31204 Qt./31104 Gal
31304 5g pail

WATER BASED/COVERAGE: One gallon covers approximately 300 square feet.

USE ON:

Processed wood such as plywood, particle board and pressed wood.

LIMITATIONS:

Safecoat paints are made without formaldehyde preservatives. Do not contaminate. Store in air-tight containers. Do not use when indoor temperature is below 55 degrees F. Do not freeze.

Thick application, high humidity or conditions other than normal will cause Safecoat to dry and cure more slowly.

SURFACE PREPARATION:

Clean surfaces of dirt, grease, mildew and oil. Surface should be completely dry before application. **Always spot test for adhesion over prior coatings.**

APPLICATION:

Before using, stir Safecoat Safe Seal by gently rolling container to avoid air bubbles. Then apply as is, using a sponge, squeegee or appropriate spray equipment. It is important to apply in very thin coats. Due to the softness of Safe Seal, multiple coats can remain slightly tacky.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

DRYING/CURING TIME:

Re-coatable after 2 hours in normal conditions. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 55 degrees F

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description: Low odor, mildly alkaline, white
% Volatile by Volume: 82.46%
Solubility in Water: Dilutable
% Volatile by Weight: 82.00%
VOC Material: 12g/l
VOC Material less H2O: 64g/l
HAP's (Hazardous Air Pollutants) zero

If you are chemically sensitive, always test for personal tolerance.

Test samples available here:

www.thegreendesigncenter.com/product/afm-2oz-samples/



LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.