

Interior/Exterior Water Based

DuroStain Pro

Safecoat DuroStain Pro protects and enhances the richness and warmth of wood without exposing your family to toxic chemicals.

Use on wooden furniture, floors and millwork.

Formulated for everyone needing the healthiest alternative.

■ Low Odor/Low 5g/1 VOC

Zero HAP's (Hazardous Air Pollutants)

■ Easy Brush Application

The finish of stained wood is actually a blend of several factors -wood species - the wood's natural color and texture - stain color - and lighting and method of application. Although these are photographs of stain on white oak wood samples, it is not possible to reproduce with printing inks the actual color of the stain. In order to determine the stains final effect, test the color on the wood to be finished.




General instructions for achieving the best results applying DuroStain Pro water-based wood stain:


- 1 Prepare the surface by scrubbing with a 50:50 mix of denatured alcohol and water using a Scotch Brite Pad.
- 2 After dry, lightly sand with fine-grade (220-320) foam sanding pad or 400-grit sandpaper.
- 3 Wipe off dust with an oil-free tack cloth or a water-dampened rag.
- 4 Test the color on the underside of the project before you begin.
- 5 Apply stain in the direction of the grain with a brush or pad applicator.
- 6 Allow the stain to penetrate 2-3 minutes to achieve the desired color.
- 7 Remove stain that has not absorbed into the wood with a clean cloth.
- 8 Protect the project with one of the Safecoat Clear Finishes.




walnut



cedar




nutmeg



golden oak



pickled




mahogany



oak



ironwood



pecan



granite

