

Installation Guidelines

If you are chemically sensitive, always test for personal tolerance.

USE ON:

Painted surfaces, raw or varnished/ lacquered wood-work or cabinetry, MDF, plywood, OSB

DO NOT USE ON:

Any metals, plastic, glass, fabric, or vinyl.

NOTE: If you don't see your surface listed here, test with a sample first to be certain that it bonds and covers properly.

SURFACE PREPARATION:

Clean surfaces of dirt, grease, mildew and oil.
Surface should be completely dry before application.

COVERAGE:

One gallon covers approximately 300-400 sf based on surface porosity.

APPLICATION:

Before using, stir Safecoat Hard Seal well, then apply as is. Apply with a brush or sprayer. It is recommended to do a light sanding between coats to improve intercoat adhesion.

Spraying Instructions:

- Reduce with up to 1/2 pint of water/gallon as needed.
- Airless sprayers should use 17/1000 to 21/1000 tip
- Reversible tips are best
- Use only 30 mesh high pressure filters
- For best coverage, spray 18" from surface
- Overlap preceding coat with 1/4 to 1/2 the fan width.

DRYING/CURING TIME:

Re-coatable after 2 hours in normal conditions. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 55 degrees F.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution. Any unused paint should be stored in air tight container for reuse. Or, add kitty litter to solidify in the can or roll out on a piece of cardboard and leave to dry before disposing. Do not flush excess paint down the sink or toilet.

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description:	Low odor, milky
Sheen Value @60°	80+
Solubility in Water:	Dilutable
Sheen Value @60°	80+
VOC Material:	21 g/l
VOC Material less H2O:	100 g/l

HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**

Test samples available through your AFM dealer.



Safecoat paints are made without formaldehyde preservatives and are HAPs free. Do not contaminate. Do not use when indoor temperature is below 55 degrees F. Do not freeze.

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.

American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.