

Installation Guidelines

If you are chemically sensitive, always test for personal tolerance.

71850 - 10.1 tube

USE ON:

Wood and metal frame construction interior and exterior paneling, Drywall and gypsum-board. Bonds cove base, tub surrounds and fiberglass. Works on landscape blocks, concrete, masonry, ceramic tile and ceiling tile. Excellent for decorative brick and stone, wood decking and sub-floor installation. Can be used with EPS direct to cured concrete. **Product is best used within six months of purchase.**

SURFACE PREPARATION:

Surface must be completely dry and stable prior to application. Remove all dirt, dust, oils, grease, wax, dried out fillers, powdery residue and other foreign materials. Use alcohol to clean surfaces if necessary.

APPLICATION:

Apply beads of adhesive to clean bonding surfaces using a standard caulking gun and assembly, making sure bonded materials are tightly joined. Use mechanical fasteners as needed to fixture materials, or as specified by code. Keep tube closed and tip covered when not in use. Because Safecoat does not use toxic mildewcides, fungicides, preservatives or solvent softening agents, material can solidify if unused with one year of purchase.

COVERAGE:

10.1 oz. tube covers approximately 25 linear feet at .25" thickness.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution. Dried material may require alcohol for cleaning.

DRYING/CURING TIME:

Allow 24 hours for a full cure.

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Boiling Point:	NA
Melting Point:	N/A
Volatile by Volume:	0%
% Volatile by Weight:	0%
VOC Material:	Less than 35 g/l @240°

HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**



Safecoat products are made without formaldehyde preservatives and are HAPs free. Do not contaminate. Do not use when indoor temperature is below 55 degrees F. Do not freeze.

LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. **American Formulating and Manufacturing** 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.